



## Test Report

No.SDHL2104006486FT

Date: May 18, 2021

Page 1 of 7

DOREL HOME FURNISHINGS EUROPE LTD  
BUILDING 4,IMPERIAL PLACE,MAXWELL ROAD,,BOREHAMWOOD,HERTFORDSHIRE,  
WD6 1JN,UNITED KINGDOM

Sample Description : NG ATHENA DESK BLACK MARBLE  
Ref. No/Item No. : 9618899COMNUK  
Buyer : DOREL HOME FURNISHINGS EUROPE LTD  
Manufacturer : COLOR STAR PRODUCTS CO. LTD.  
Supplier : COLOR STAR PRODUCTS CO. LTD.  
Country of Origin : CHINA  
Country of Destination : UNITED KINGDOM

As above test item and its relevant information regarding to the submission are provided and confirmed by the applicant. SGS is not liable to either the test item or its relevant information, in terms of the accuracy, suitability, reliability or/and integrity accordingly.

\*\*\*\*\*

Sample Receiving Date : Apr 17, 2021  
Test Performing Date : Apr 22, 2021 to Apr 27, 2021  
Test Performed : Selected test(s) as requested by applicant

### Test Result Summary

| No.                                                        | Test(s) Requested                               | Result(s) | Comments |
|------------------------------------------------------------|-------------------------------------------------|-----------|----------|
| 1                                                          | BS EN 12521:2015, excluding information for use | PASS      | /        |
| For further details, please refer to the following page(s) |                                                 |           |          |

Signed for and on behalf of  
SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch

Bill Wang  
Authorized Signatory

scan to see the report



SDHL2104006486FT



SGS-CSTC Standards Technical Services Co., Ltd.  
Shunde Branch Harbin

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

1/F, 1st Building, European Industrial Park, No.1 Shunde South Road, Wusha Section, Daliang Town, Shunde, Foshan, Guangdong, China 528333 t (86-757) 22805888 f (86-757) 22805858 www.sgs.com.cn  
中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757) 22805888 f (86-757) 22805858 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

**TESTS AND RESULTS**
**Test Conducted:**

BS EN 12521:2015 Furniture – Strength, durability and safety – Requirements for domestic tables, excluding information for use.

**No. of Sample:**

1 piece (Sample #1). For more sample information and pictures, please refer to the following page.

**Table Type:**

- ☐ Tables less than or equal to 600 mm in height, or Tables with tops with a surface area less than or equal to 0.25 m<sup>2</sup>;  
☒ All other tables.

| Test and Requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Test Results |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>5 Safety requirements</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |              |
| <b>5.1 General requirements</b><br>The table shall be so designed as to minimize the risk of injury to the user.<br>All parts of the table with which the user comes into contact during intended use shall be so designed that physical injury and damage are avoid.<br>There requirements are met when<br>1) the edges of table tops which are directly in contact with the user shall be rounded or chamfered. All other edges accessible during use shall be free from burrs and/or sharp edges<br>2) the ends of hollow components are closed or capped.<br>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.<br>It shall not be possible for any load bearing part of the table to come loose unintentionally.<br>All parts that are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use. | PASS         |
| <b>5.2 Shear and squeeze points</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |
| <b>5.2.1 Shear and squeeze points when setting up and folding</b><br>Unless 5.2.2 or 5.2.3 are applicable, shear and squeeze points, as defined in 3.3, that are created only during setting up and folding, including the installation of extensions to the main table surface are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.<br>The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 5.1.                                                                                                                                                                                                                                                                                                                              | N/A          |
| <b>5.2.2 Shear and squeeze points under the influence of powered mechanisms</b><br>There shall be no shear and squeeze points created by parts of the table operated by powered mechanisms, i.e. springs, gas lifts and motorized systems.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | N/A          |
| <b>5.2.3 Shear and squeeze points during use</b><br>There shall be no shear and squeeze points created by forces applied during normal use.<br>There shall be no shear and squeeze points if a hazard is created by the user during normal movements and actions, e.g. attempting to move the table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | PASS         |



SGS-CTC (Shunde) Technical Services Co., Ltd.  
Shunde Branch Harbin

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1/F, 1<sup>st</sup> Building, European Industrial Park, No.1 Shunde South Road, Wusha Section, Daliang Town, Shunde, Foshan, Guangdong, China 528333 t (86-757)22805888 f (86-757)22805858 www.sgs.com.cn  
 中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805858 e sgs.china@sgs.com

| Test and Requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Test Results |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <p><b>6 Stability, strength and durability (With reference to the test methods of EN 1730:2012)</b><br/>           Tables shall be tested for stability, strength and durability according to and following the order as below.<br/>           The table shall fulfill the following requirements after tested.<br/>           1) there are no fractures of any member, joint or component,<br/>           2) there is no loosening of joints intended to be rigid,<br/>           3) the table fulfils its functions after removal of the test loads,<br/>           4) the table shall not tip over.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |
| <p><b>EN 1730, 6.2 Horizontal Static Load Test</b><br/>           Apply a mass of 50 kg to an area of <math>(300 \pm 50)</math> mm x <math>(300 \pm 50)</math> mm, or a diameter of <math>(300 \pm 50)</math> mm, to the approximate centre of the table top.<br/>           Apply the horizontal force of <input type="checkbox"/> 200 N / <input checked="" type="checkbox"/> 400 N by means of the loading pad (Dia=100 mm) at the table top level in a direction perpendicular to a line joining the two legs/supports, midway between the legs/supports.<br/>           One application of the force in each direction (total 4 directions) represents one cycle.<br/>           Repeat the above operation for 10 cycles.<br/> <b>Note:</b><br/> <i>If the table top is not secured to the understructure and the top moves when the specified force is applied, reduce the force sufficiently to just prevent movement. Record the force applied. The applied force shall not be reduced below the minimum specified force of <input type="checkbox"/> 100 N / <input checked="" type="checkbox"/> 200 N.</i><br/> <i>If the unrestrained base lifts when the specified force is applied, reduce the force sufficiently to just prevent lifting. Record the force applied. The applied force shall not be reduced below the minimum specified force of <input type="checkbox"/> 100 N / <input checked="" type="checkbox"/> 200 N. If unrestrained base lifts at this force, the specified mass applied to the table top shall be increased gradually until this tendency ceases.</i></p> | <p>PASS</p>  |
| <p><b>EN 1730, 6.3 Vertical Static Load Tests</b><br/>           Tables with extension pieces shall be tested both in the extended and unextended configurations. A table extension added in the centre of the table shall be tested as the main surface. A part of the main surface in the unextended configuration can become an ancillary surface in the extended configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |              |
| <p><b>EN 1730, 6.3.1 Vertical static load on main surface</b><br/>           Apply the vertical force of <math>F_v</math> using the loading pads 100 mm in diameter on the top that is likely to cause a failure, but not less than 100 mm from any edge for 10 times.<br/>           If the table tends to overturn gradually, move the loading point towards the centre of the table until this tendency ceases.<br/>           (1) If height of main surface <math>\leq 600</math> mm, <math>F_v =</math> <input type="checkbox"/> 1000 N / <input checked="" type="checkbox"/> -- N;<br/>           (2) If height of main surface <math>&gt; 600</math> mm, <math>F_v =</math> <input type="checkbox"/> 250 N / <input checked="" type="checkbox"/> 1000 N;</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | <p>PASS</p>  |
| <p><b>EN 1730, 6.3.2 Additional vertical static load test where the main surface has a length <math>&gt; 1600</math> mm</b><br/>           Apply two vertical downward forces <math>F_v</math> simultaneously using the loading pad (Dia=100 mm) at points positioned on the longitudinal axis of the table top, 400 mm on either side of the transversal axis for 10 times.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <p>N/A</p>   |
| <p><b>EN 1730, 6.3.3 Vertical static load on ancillary surface (Only for all other tables)</b><br/>           Apply a vertical downward force of <input type="checkbox"/> -- N / <input checked="" type="checkbox"/> 200 N using the loading pad (Dia=100 mm) anywhere on the ancillary surface that is likely to cause a failure, but not less than 100 mm from any edge for 10 times.<br/>           If the article tends to overturn, load the main table top gradually to prevent overturning.<br/>           If there are several such positions repeat the test at a maximum of two different positions.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | <p>N/A</p>   |



| Test and Requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Test Results |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>EN 1730, 6.4 Horizontal Durability Test</b><br>Place a mass of 50 kg on the geometric center of the table top. Apply two alternating horizontal forces of <input type="checkbox"/> 150 N / <input checked="" type="checkbox"/> 300 N using the loading pads 100 mm in diameter alternately at the top surface of the table for <input type="checkbox"/> 5,000 / <input checked="" type="checkbox"/> 10,000 cycles. One force is at one end of the table 50 mm from the corner and the other at the opposite end. Repeat above operation at the other corners.<br><b>Note:</b><br><i>If the table top is not secured to the understructure and the top moves when the specified force is applied, reduce the force sufficiently to prevent movement. Perform the test using this reduced force in that direction only. Record the value of any reduced force used.</i><br><i>If the table tends to lift in one direction of loading at a load less than that specified, reduce the horizontal force to the value determined at the beginning of the test process. Perform the test using this reduced force in that direction only. Record the value of any reduced force used.</i> | PASS         |
| <b>EN 1730, 6.5 Vertical Durability Test for cantilever or pedestal tables (Only for all other tables)</b><br>Apply the vertical force of 300 N using the loading pads 100 mm in diameter on the top of the table at any position that is not less than 100mm from any edge. Repeat above operation for <input type="checkbox"/> -- / <input checked="" type="checkbox"/> 10,000 times.<br><b>Note:</b><br><i>Tables with extensions inserted in the centre shall be tested in the extended configuration. All other tables shall be tested without extending ancillary surfaces.</i><br><i>If the article tends to lift, load the centre of the main table top with a mass sufficient to prevent overturning.</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | N/A          |
| <b>EN 1730, 6.6.1 &amp; 6.6.3 Vertical Impact Test for tables without glass in their construction</b><br>Place one layers of 25 mm thick polyether foam on the table top. The height of drop shall be measured from the position where the impactor is resting on the surface of that layer of foam. Place a second layer of 25 mm thick polyether foam between the striking surface and the table top. Allow the 25 kg impactor to fall freely from the height of <input type="checkbox"/> 140 mm / <input checked="" type="checkbox"/> 180 mm onto the table top at any position within 100 mm from the edge for 10 times.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | PASS         |
| <b>EN 1730, 6.6.1 &amp; 6.6.2 Vertical Impact Test for tables with glass in their construction – safety glass</b><br>Place a piece of 100 mm thick polyether foam sheet between the striking surface and the table top. Allow the 25 kg impactor to fall freely from the height of <input type="checkbox"/> 140 mm / <input checked="" type="checkbox"/> 180 mm onto the table top at any within position 100 mm from the edge for 10 times.<br><b>Note:</b><br><i>Glass is considered to be safety glass if the glass fulfils the requirements in EN 12150-1:2015, Clause 8, fragmentation test, or where the mode of breakage (<math>\beta</math>) according to EN 12600:2002, is Type B or Type C.</i><br><i>Impact the table top in accordance with the positions defined within EN 1730:2012, 6.6.3.</i>                                                                                                                                                                                                                                                                                                                                                                         | N/A          |



| Test and Requirements                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Test Results |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <p><b>EN 14072:2003, 6 Vertical Impact Test for tables with glass in their construction – other glass</b></p> <p>Place a piece of 100 mm thick polyether foam sheet between the striking surface and the table top. Allow the 25 kg impactor to fall freely from the height of <input type="checkbox"/> 180 mm / <input checked="" type="checkbox"/> 240 mm onto the table top at any position within 100 mm from the edge for 10 times.<br/> <i>Note: Impact the table top in accordance with the positions defined within EN 1730:2012, 6.6.3.</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | N/A          |
| <p><b>EN 1730, 7.1 &amp; 7.2 Stability under Vertical Load</b></p> <p>Apply the vertical force of <math>F=L/4</math> (N) at the position 50 mm from the outer edge of the tabletop on the side where the load is most likely to cause overturning as far away from the support as possible.<br/>         If the table (<i>only for all other table</i>) has an ancillary surface, <math>F'=L'/8</math> (N) shall be applied at the specified positions of ancillary surface;<br/>         When <math>L</math> or <math>L' \leq 800</math> mm, <math>F</math> or <math>F'=V1</math>;<br/>         When <math>L</math> or <math>L' &gt; 1600</math> mm, <math>F</math> or <math>F'=V2</math>;<br/>         Main surface: Small table: <math>V1=200N</math>, <math>V2=400N</math>; Other table: <math>V1=200N</math>, <math>V2=400N</math>;<br/>         Ancillary surface: Small table: Not applicable; Other table: <math>V1=100N</math>, <math>V2=200N</math>;<br/> <math>L</math> is the longest dimension of the table top in the overturning direction;<br/> <math>L'</math> is the longest dimension of the ancillary surface in the overturning direction;<br/> <i>Note:</i><br/>         Tables that are or can be set to a height greater than 950 mm shall not overturn when tested according to 7.2.2 using 50 % of the specified vertical load (V).<br/> <i>Tables with extension pieces shall be tested both in the extended and unextended configurations. A table extension added in the centre of the table shall be tested as the main surface. A part of the main surface in the unextended configuration can become an ancillary surface in the extended configuration.</i><br/> <i>For tables that might not fulfil the stability requirements before carrying out any tests, the applicable stability tests shall be carried out before starting the sequence of tests specified in this table.</i></p> | PASS         |
| <p><b>5.3.2 Stability for tables with extension elements (Only for all other tables)</b></p> <p>Load each extension element with the load specified.<br/>         For tables with extension elements not fitted with interlocks open all extension elements in the least favourable combination. For tables with extension elements fitted with interlocks open the two extension elements with the largest loads without overriding the interlock. If an interlock device prevents any two of the extension elements from being opened simultaneously, open the extension element with the largest load.<br/>         The table shall not overturn when the vertical force of <input type="checkbox"/> -- / <input checked="" type="checkbox"/> 200 N is applied at the centre of the front of the table, 50 mm from the edge.<br/> <i>Note: For tables that might not fulfil the stability requirements before carrying out any tests, the applicable stability tests shall be carried out before starting the sequence of tests specified in this table.</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | N/A          |
| <p><b>7 Information for use</b></p> <p>Information for use shall be available in the language of the country in which it will be delivered to the end user. It shall contain at least the following details:<br/>         a) assembly instructions, where applicable,<br/>         b) instructions for the care and maintenance of the table.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | N/R          |



### Remark:

1. N/A – Not applicable; N/R – Not requested; N/P – Not provided.
2. For the sample information and pictures, please refer to the following page.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC (Shunde) Technical Services Co., Ltd.  
Shunde Branch Harbin

1/F, 1<sup>st</sup> Building, European Industrial Park, No.1 Shunde South Road, Wusha Section, Daliang Town, Shunde, Foshan, Guangdong, China 528333 t (86-757)22805888 f (86-757)22805858 www.sgs.com.cn  
中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号厂房首层 邮编: 528333 t (86-757)22805888 f (86-757)22805858 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

### SAMPLE INFORMATION AND PICTURES

**Weight:** 15.40 kg

**Overall Dimensions:** 500 mm D x 990 mm W x 770 mm H

**Other Dimensions:** /

#### Sample as Received



View 1



View 2



View 3



View 4

\*\*\*End of Report\*\*\*



SGS-CSTC Shunde Branch Technical Services Co., Ltd.  
Shunde Branch Harbin

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

1/F, 1<sup>st</sup> Building, European Industrial Park, No.1 Shunde South Road, Wusha Section, Daliang Town, Shunde, Foshan, Guangdong, China 528333 t (86-757) 22805888 f (86-757) 22805858 www.sgs.com.cn  
中国·广东·佛山市顺德区大良街道办事处五沙顺和南路1号欧洲工业园一号楼首层 邮编: 528333 t (86-757) 22805888 f (86-757) 22805858 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)