

**DOREL HOME FURNISHINGS EUROPE LTD**

BUILDING 4, IMPERIAL PLACE MAXWELL ROAD BOREHAMWOOD WD6 1JN UNITED KINGDOM


The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. Results apply to the sample as received.

Sample Description	WARNER CHAIR
Style / Item No.	AOC6732-JLP
Buyer Name	JOHN LEWIS PARTNERSHIP UK
Supplier Name	DOREL HOME FURNISHINGS EUROPE LTD
Manufacturer Name	ZHEJIANG HENGLIN CHAIR IND.CO
Country of Origin	CHINA
Country of Destination	UK
Sample Receiving Date	NOV 09, 2021
Test Performing Date	NOV 09, 2021 TO DEC 10, 2021

**Test Result Summary**

Test(s) Requested	Result(s)
BS EN 1335-2:2018 Excluding Clause 6 information for use	PASS
<b>Remark:</b>	
1. This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.	
2. For further details, please refer to the following page(s).	

Signed for and on behalf of  
SGS-CSTC Co., Ltd. Anji Branch




David Fan  
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

**Test Conducted: BS EN 1335-2:2018 Office furniture- Office work chair- Part 2: Safety requirements**

**Test Result:**

Test Item	Test Method & Test Requirement	Test Result
<b>Safety requirements (BS EN 1335-2:2018, 4)</b>		
<p>General (BS EN 1335-2:2018, 4.1)</p>	<p>The chair shall be so designed as to minimise the risk of injury to the user. All parts of the chair with which the user comes into contact during intended use, shall be so designed that physical injury and damage to property are avoided. These requirements are fulfilled when: a) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded with minimum 2 mm radius; b) the edges of handles are rounded or chamfered in the direction of the force applied; c) all other edges and corners are free from burrs and rounded or chamfered; d) the ends of accessible hollow components are closed or capped. Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall be possible to operate the adjusting devices from sitting position in the chair. It shall not be possible for any load bearing part of the chair to come loose unintentionally.</p>	<p>PASS</p>
<b>Shear and squeeze points (BS EN 1335-2:2018, 4.2)</b>		
<p>Shear and squeeze points under influence of powered mechanisms (BS EN 1335-2:2018, 4.2.1)</p>	<p>There shall be no accessible shear and squeeze points created by parts of the chair operated by powered mechanisms, i.e. springs, gas lifts and motorized systems.</p>	<p>PASS</p>
<p>Shear and squeeze points during use (BS EN 1335-2:2018, 4.2.2)</p>	<p>There shall be no accessible shear and squeeze points created by loads applied during normal use. Shear and squeeze points are not acceptable if there is a risk of injury created by the weight of the user during normal movements and actions, e.g. manipulating levers and crank handles.</p>	<p>PASS</p>



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (China) Technical Services Co., Ltd.  
Anji Branch Hardwares

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
<b>Stability tests and requirements (BS EN 1335-2:2018, 4.4)</b> When tested according to Table 1, the seating shall not overturn.		
Corner stability (BS EN 1022:2018, 7.3.3)	This test is only applicable on seating possible to apply the loading pad at the specified position. Define the loading point 60 mm from the edge of the load bearing structure on a line as specified at the corner. Apply a force $F_1$ of 300 N vertically at the loading point for $(5\pm 2)$ s. For seating with multiple seats apply the force $F_1$ at the loading point on one outside seating position.	NA
Forwards overturning (BS EN 1022:2018, 7.3.1)	Apply a force $F_1$ of 600 N (for seating with multiple seats apply two forces simultaneously) vertically at the point on the centre line of the seat 60 mm behind the front edge of the load bearing structure. Apply a force $F_2$ of 20 N horizontally outwards from the point each vertical load contacts the seat surface for $(5\pm 2)$ s. For seating with a leg rest to support the weight of the user, repeat the test procedure on the leg rest with the leg rest fully extended.	PASS
Forward overturning for chairs with footrests (BS EN 1022:2018, 7.3.2)	For seating with tubular foot rests or the foot rest depth is less than 120 mm, apply the vertical force $F_1$ of 1100 N at the most onerous point along the tube centre line or the middle of the foot rest surface. For all other seating with foot rests apply the vertical force $F_1$ of 1100 N at the most onerous point 60 mm from the edge of the foot rest. Apply a force $F_2$ of 20 N horizontally outwards from the point the vertical load contacts the foot rest surface for $(5\pm 2)$ s.	NA
Sideways overturning for chairs without arm rests (BS EN 1022:2018, 7.3.4)	This test is applicable to all seating where the top edge of the seat on the transverse plane is 50 mm or less above the height of the loaded seat loading point. Apply a force $F_1$ of 600 N vertically at a point 60 mm behind the edge of the load bearing structure on the side nearest the stopped feet and on the seat transverse plane. In the transverse plane, apply a sideways force $F_2$ of 20 N horizontally outwards from the point the vertical load contacts the seat surface for $(5\pm 2)$ s.	NA
Sideways overturning for chairs with arm rests (BS EN 1022:2018, 7.3.5.1 & 7.3.5.2)	This test is applicable to all seating with arms on the transverse plane is more than 50 mm above the seat loading point. Apply a force $F_1$ of 250 N vertically at a point 100 mm to the seat median plane nearest the stopped feet and on the transverse plane. Apply a force $F_2$ of 350 N vertically at a position on the centre line of the arm up to a maximum 40 mm inwards from the outside edge of arm structure on the transverse plane, but not less than 40 mm from the front or rear edge of the arm structure. If the transverse plane does not intersect with arm rest, apply force $F_2$ at 40 mm from the front or rear of the arm structure nearest the transverse plane. Apply a horizontal force $F_3$ of 20 N outwards and perpendicular to the line joining the stopped feet, for at least 5s, at the upper surface of the seat or arm rest in line with the vertical force $F_2$ .	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
Rearwards overturning for chairs without back rest inclination and for chairs with adjustable backrest inclination that can be locked (BS EN 1022:2018, 7.3.6)	The test is not applicable to seating that has adjustable back rest inclination that cannot be locked in position. Apply a vertical force $F_1$ of 600N to the seat at seat loading point. Apply the force $F_2$ ( $F_2 = 0.2857(1000-H)$ N, H = Height of loaded seat above the floor, in mm) for $(5 \pm 2)$ s horizontally rearwards to the seating back at back loading point B, or at the top edge of back rest, whichever is the lower. When the seating has more than one sitting place, apply the procedure on two most adverse sitting places simultaneously.	PASS
Rearwards overturning for chairs with back rest inclination (BS EN 1022:2018, 7.4.2)	The test method applies to all values of $\theta \geq 10^\circ$ and values of $\gamma$ between $90^\circ$ and $170^\circ$ . If the seating has a locking system it shall be disabled. Load the seat with 13 loading discs so that the discs are firmly settled against the back rest.	PASS
<b>Strength and durability (BS EN 1335-2:2018, 5)</b> The strength and durability requirements are fulfilled when, after testing in accordance with Table 2: a) there are no fractures of any member, joint or component; b) there is no loosening of joints intended to be rigid; and c) the chair fulfils its functions after removal of the test loads.		
Combined seat and back static load test (BS EN 1728:2012, 7.3)	Apply a vertical force $F_1$ of 1600N at point "A". Keep the seat loaded and apply a force $F_2$ of 560N at point "B". When fully loaded the force shall act at $90^\circ \pm 10^\circ$ to the back rest plane. Remove the back force and then the seat force. Repeat the operation for 10 cycles.	PASS
Seat front edge static load test (BS EN 1728:2012, 7.4)	Position the smaller seat loading pad at loading point F or J. Apply a vertical downward force of 1600N through the centre of the loading pad. Repeat the operation for 10 cycles.	PASS
Foot rest static load test (BS EN 1728:2012, 7.8)	Apply a downward force of 1300N to the seat at the seat loading point. Apply a vertical force acting 80 mm from front edge of the load bearing structure of the foot rest at those points most likely to cause failure. For round cross section ring shaped footrests, apply the force through the centre of the ring cross section. If the seating tends to overturn, increase the load on seat to a magnitude that just prevents overturning and record the load used. Repeat the operation for 10 cycles.	NA



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result																								
<p>Seat and back durability (BS EN 1728:2012, 7.9)</p>	<p>The seat load shall be applied vertically. The back rest force shall be applied at an angle of 90° ± 10° to the back rest when fully loaded. All chairs shall be tested to steps 1 to 5. Chairs with a locking device for seat and/or back rest angle movements shall be tested in step 2 first with the device locked for half of the cycles and then with the device unlocked for the other half of the cycles. In steps 3, 4 and 5 the mechanism shall be set free to move. If the back rest pad is pivoting around a horizontal axis and is free to move, the horizontal force shall be applied on the axis. If height adjustable, the axis shall be set as close as possible to 300 mm above point "A". If the axis cannot be adjusted to 300 mm, adjust the force to produce the same bending moment.</p> <table border="1" data-bbox="432 792 1238 1144"> <thead> <tr> <th>Step</th> <th>Loading point</th> <th>Force (N)</th> <th>Number of cycles</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>A</td> <td>1500</td> <td>120000</td> </tr> <tr> <td>2</td> <td>C B</td> <td>1200 320</td> <td>80000</td> </tr> <tr> <td>3</td> <td>J E</td> <td>1200 320</td> <td>20000</td> </tr> <tr> <td>4</td> <td>F H</td> <td>1200 320</td> <td>20000</td> </tr> <tr> <td>5</td> <td>D and G (alternating)</td> <td>1100</td> <td>20000</td> </tr> </tbody> </table>	Step	Loading point	Force (N)	Number of cycles	1	A	1500	120000	2	C B	1200 320	80000	3	J E	1200 320	20000	4	F H	1200 320	20000	5	D and G (alternating)	1100	20000	<p>PASS</p>
Step	Loading point	Force (N)	Number of cycles																							
1	A	1500	120000																							
2	C B	1200 320	80000																							
3	J E	1200 320	20000																							
4	F H	1200 320	20000																							
5	D and G (alternating)	1100	20000																							
<p>Armrests durability (BS EN 1728:2012, 7.10)</p>	<p>Apply the force of 400N on each arm rest at the point most likely to cause failure, but not less than 100 mm from the front or rear edge of the arm rest length and through the centre of the width of the arm rest, but not more than 100 mm from the inner edge of the arm rest. Apply the force to both arm rests simultaneously for seating with only one seating position and to one arm rest only for seating with multiple seating positions. Repeat the test for 60000 cycles.</p>	<p>PASS</p>																								
<p>Armrest downward static load test – central (BS EN 1728:2012, 7.5)</p>	<p>Apply the force to both arm rests simultaneously and vertically at the middle point of the arm rest length and centred side to side. In the case of an arm rest which is not horizontal, or which is curved, the length is measured in a horizontal plane 20 mm below the highest point of the arm rest. Test force (N): 750 Number of cycles: 5 Test force (N): 900 Number of cycles: 5</p>	<p>PASS</p>																								



Test Item	Test Method & Test Requirement	Test Result
<b>Rolling resistance test and requirements (BS EN 1335-2:2018, 5.3)</b>		
Rolling resistance test and requirements (BS EN 1335-2:2018, 5.3)	<p>The unloaded chair shall be tested for rolling resistance according to BS EN 1728:2012, 6.30 and shall fulfil the following requirements:</p> <p>a) the castors shall be of identical construction;                      b) the rolling resistance shall be <math>\geq 12</math> N.</p> <p>The chair shall be placed on the test floor and shall be pushed or pulled over a distance of at least 550 mm. A speed of <math>(50 \pm 5)</math> mm/s shall be maintained over the measuring distance. The force shall be applied at a height of <math>(200 \pm 50)</math> mm above the test surface. Record the force used to push or to pull the chair over the distance from 250 mm to 500 mm as the rolling resistance.</p>	PASS
<b>Information for use (BS EN 1335-2:2018, 6)</b>		
Information for use (BS EN 1335-2:2018, 6)	<p>Information for use shall be available in the language of the country in which the product will be available to the end user. It shall contain at least the following details:</p> <p>a) information regarding the intended use;                      b) information regarding possible adjustments;                      c) instruction for operating the adjusting mechanisms;                      d) instruction for the care and maintenance of the chair;                      e) information for chairs with seat height adjustments with energy accumulators that only trained personnel may replace or repair seat height adjustment components with energy accumulators;                      f) information on the choice of castors in relation to the floor surface.</p>	NT
<b>Functional tests (BS EN 1335-2:2018, Annex A)</b>		
Arm rest downward static load test – front (BS EN 1728:2012, 7.6)	Apply the force of 450N to both arm rests simultaneously and vertically acting at 75 mm from the front edge and centred side to side. Repeat the operation for 5 cycles.	PASS
Arm rest sideways static load test (BS EN 1728:2012, 7.7)	Apply an outward force of 400N to one arm rest or to each arm rest of the unit simultaneously at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. Repeat the operation for 10 cycles.	PASS
Swivel test (BS EN 1728:2012, 7.11)	The base of the chair shall be secured on a rotating table so that the rotating axis of the chair coincides with the rotating axis of the table. The upper part of the chair shall be loosely fixed in such a way as not to hinder the rotation of the base. Load the seat in loading point A with a mass $M_1$ of 60kg and in loading point C with a mass $M_2$ of 35kg. The angle of rotation shall be $360^\circ$ at a rate of $(10 \pm 5)$ cycles/minute. Change direction after each rotation. Repeat the operation for 12000 cycles.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (China) Technical Services Co., Ltd. | No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 | t: (86-572) 5018825 f: (86-572) 5018829 | www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 | 邮编: 313300 | t: (86-572) 5018825 f: (86-572) 5018829 | e: sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
<p>Foot rest durability (BS EN 1728:2012, 7.12)</p>	<p>Apply the specified downward force of 900N to the seat at the seat loading point. Apply a vertical force of 900N acting 80 mm from front edge of the load bearing structure of the foot rest at those points most likely to cause failure. For round cross section ring shaped footrests, the force shall be applied through the centre of the ring cross section. If the seating tends to overturn, increase the load on seat to a magnitude that just prevents overturning and record the load used. Repeat the operation for 50000 cycles.</p>	<p>NA</p>
<p>Castor and chair base durability (BS EN 1728:2012, 7.13)</p>	<p>Not apply to chairs with castors which are braked when the chair is loaded. The chair shall be placed on a rotating table so that the rotating axis of the chair coincides with the rotating axis of the table. Load the seat in point A with M<sub>1</sub> of 110 kg. The base shall be loosely fixed in such a way that there is no rotation of the base but that the natural movements of the castors are not prevented. The castors shall be left free to swivel, the table shall be rotated with a rate of 6 cycles per minute. The angle of rotation shall be from 0° to 180° and back. One rotation forward and one rotation backward constitutes one cycle. Repeat the operation for 36000 cycles.</p>	<p>PASS</p>

**Remark:**

1. NA = Not applicable; NT = Not tested



SGS-CSTC (China) Technical Services Co., Ltd.  
Anji Branch Hardlines

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

**Sample Information**

Overall dimension: 715 mm (L)×673 mm (W)×968 mm -1062 mm (H)  
 Radius of base: 345 mm  
 Weight: 15.0 kg

**Photo Appendix**



Sample as received - View 1



Sample as received - View 2



Sample as received - View 3



Sample as received - View 4

SGS authenticate the photo on original report only

\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com