

Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 1 of 11

DOREL HOME FURNISHINGS EUROPE LTD

BUILDING 4, IMPERIAL PLACE, MAXWELL ROAD, BOREHAMWOOD, HERTFORDSHIRE. WD6 1JN

THIS TEST REPORT IS TO SUPERSEDE TEST REPORT NO.: AJHL2102000422FT, DATE: FEB 20, 2021


The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. Results apply to the sample as received.

*Sample Description	ADALYNN CONVERTIBLE FUTON
Style / Item No.	2288009QEUK(7607-3)
Buyer Name	DOREL HOME FURNISHINGS EUROPE LTD
Manufacturer Name	JIAXING ANYEE INTELLIGENT FURNITURE CO., LTD.
Country of Origin	CHINA
Country of Destination	UK
Sample Receiving Date	FEB 08, 2021
*Sample Re-submitted Date	MAR 30, 2021
*Test Performing Date	FEB 08, 2021 TO MAR 31, 2021

Test Result Summary

Test(s) Requested	Result(s)
EN 12520:2015 Excluding Clause 6 information for use	PASS
*EN 1725:1998	PASS
*Durability operation for 3650 cycles (In accordance with EN 13759:2012 Furniture – Operating mechanisms for seating and sofa-beds – Test methods)	PASS
Remark: 1. This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included. 2. For further details, please refer to the following page(s).	

Signed for and on behalf of
SGS-CSTC Co., Ltd. Anji Branch




David Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 2 of 11

Test Conducted: EN 12520:2015 Furniture - Strength, durability and safety – Requirements for domestic seating

Test Result:

Test Item	Test Method & Test Requirement	Test Result
General requirements (EN 12520:2015, 5.1)		
General requirements (EN 12520:2015, 5.1)	All parts of the seating with which the user comes into contact, during intended use, shall be designed to ensure that physical injury and damage are avoided. These requirements are met when: a) edges of the seat, back rest and arm rests, which are in contact with the user when sitting are rounded or chamfered. All other edges accessible during use shall be free from burrs and/or sharp edges; b) ends of hollow components are closed or capped. Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall not be possible for any load bearing part of the seating to come loose unintentionally. All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.	PASS
Shear and squeeze points (EN 12520:2015, 5.2)		
Shear and squeeze points when setting up and folding (EN 12520:2015, 5.2.1)	Unless 5.2.2 or 5.2.3 are applicable, shear and squeeze points, as defined in 3.3, that are created only during setting up and folding, including tipping seat, are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain. The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 5.1.	PASS
Shear and squeeze points under the influence of powered mechanisms (EN 12520:2015, 5.2.2)	With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating under powered mechanisms e.g. springs and gas lifts. NOTE: Electrically operated seating is covered by EEC Directives for EMC, Machinery, Low Voltage or Medical Devices.	NA
Shear and squeeze points during use (EN 12520:2015, 5.2.3)	There shall be no shear and squeeze points created by loads applied during normal use. The loads applied during normal use can be found in Table 1. Shear and squeeze points are not acceptable if a hazard is created by the weight of the user during normal movements and actions, e.g. attempting to move the seating by lifting the seat or by adjusting the backrest. NOTE: This hazard is best prevented by the use of automatic locking mechanisms.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 3 of 11

Test Item	Test Method & Test Requirement	Test Result
Stability (EN 12520:2015, 5.3)		
The seating shall fulfil the relevant requirements of EN 1022.		
All seating except loungers (EN 1022:2018, 7)		
General (EN 1022:2018, 7.1)	The stability tests are not applicable to seating which has both the height of the seat loading point < 200 mm and a mass < 5 kg.	/
Test procedures, all seating (EN 1022:2018, 7.3)		
Forwards overturning (EN 1022:2018, 7.3.1)	Apply a force F_1 of 600 N (for seating with multiple seats apply two forces simultaneously) vertically at the point on the centre line of the seat 60 mm behind the front edge of the load bearing structure. Apply a force F_2 of 20 N horizontally outwards from the point each vertical load contacts the seat surface for (5 ± 2) s. For seating with a leg rest to support the weight of the user, repeat the test procedure on the leg rest with the leg rest fully extended. The seating shall not overturn.	PASS
Forwards overturning for seating with foot rest (EN 1022:2018, 7.3.2)	For seating with tubular foot rests or the foot rest depth is less than 120 mm, apply the vertical force F_1 of 600 N at the most onerous point along the tube centre line or the middle of the foot rest surface. For all other seating with foot rests apply the vertical force F_1 of 600 N at the most onerous point 60 mm from the edge of the foot rest. Apply a force F_2 of 20 N horizontally outwards from the point the vertical load contacts the foot rest surface for (5 ± 2) s. The seating shall not overturn.	NA
Corner stability test (EN 1022:2018, 7.3.3)	This test is only applicable on seating possible to apply the loading pad at the specified position. Define the loading point 60 mm from the edge of the load bearing structure on a line as specified at the corner. Apply a force F_1 of 300 N vertically at the loading point for (5 ± 2) s. For seating with multiple seats apply the force F_1 at the loading point on one outside seating position. The seating shall not overturn.	PASS
Sideways overturning, all seating without arm rests (EN 1022:2018, 7.3.4)	This test is applicable to all seating where the top edge of the seat on the transverse plane is 50 mm or less above the height of the loaded seat loading point. Apply a force F_1 of 600 N vertically at a point 60 mm behind the edge of the load bearing structure on the side nearest the stopped feet and on the seat transverse plane. In the transverse plane, apply a sideways force F_2 of 20 N horizontally outwards from the point the vertical load contacts the seat surface for (5 ± 2) s. The seating shall not overturn.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
Sideways overturning, all other seating with arm rests (EN 1022:2018, 7.3.5.2)	This test is applicable to all seating with arms on the transverse plane is more than 50 mm above the seat loading point. Apply a force F_1 of 250 N vertically at a point 100 mm to the seat median plane nearest the stopped feet and on the transverse plane. Apply a force F_2 of 350 N vertically at a position on the centre line of the arm up to a maximum 40 mm inwards from the outside edge of arm structure on the transverse plane, but not less than 40 mm from the front or rear edge of the arm structure. If the transverse plane does not intersect with arm rest, apply force F_2 at 40 mm from the front or rear of the arm structure nearest the transverse plane. Apply a horizontal force F_3 of 20 N outwards and perpendicular to the line joining the stopped feet, for at least 5s, at the upper surface of the seat or arm rest in line with the vertical force F_2 . The seating shall not overturn.	NA
Sideways overturning, all other seating with raised side edges (EN 1022:2018, 7.3.5.3)	This test is applicable to all seating where the seat top edge on the transverse plane is more than 50 mm above the seat loading point. Apply a force F_1 of 250 N vertically at a point 100 mm to the seat median plane nearest the stopped feet and on the transverse plane. Apply a force F_2 of 350 N at a position no greater than 40 mm inwards from the outside edge of the raised edge on the side nearest the stopped feet and on the transverse plane. If the distance between the loading points is less than 200 mm, apply a force that provides the same overturning moment of the combined forces F_1 and F_2 at the most suitable point on the transverse plane. Apply a horizontal force F_3 of 20 N outwards and perpendicular to the line joining the stopped feet, for (5 ± 2) s, at the upper surface of the raised edge in line with vertical force F_2 . The seating shall not overturn.	NA
Rearwards overturning all seating with back rests (EN 1022:2018, 7.3.6)	The test is not applicable to seating that has adjustable back rest inclination that cannot be locked in position. Apply a vertical force F_1 of 600N to the seat at seat loading point. Apply the force F_2 ($F_2 = 80$ N if $H \geq 720$ mm; $F_2 = 0.2857(1000-H)$ N if $H < 720$ mm. H = Height of loaded seat above the floor, in mm) for (5 ± 2) s horizontally rearwards to the seating back at back loading point B, or at the top edge of back rest, whichever is the lower. When the seating has more than one sitting place, apply the procedure on two most adverse sitting places simultaneously. The seating shall not overturn.	PASS
Additional test procedures for seating with reclining back rests (EN 1022:2018, 7.4)		
Tilt chairs (EN 1022:2018, 7.4.2)	The test method applies to all values of $\theta \geq 10^\circ$ and values of γ between 90° and 170° . If the seating has a locking system it shall be disabled. Load the seat with 11 loading discs so that the discs are firmly settled against the back rest. Apply the loads for (120 ± 60) s. The seating shall not overturn.	NA



Test Item	Test Method & Test Requirement	Test Result
Reclining seating with leg rest (EN 1022:2018, 7.4.3)	The test method applies to all values of $\theta \geq 10^\circ$ and less than 55° and values of γ between 90° and 170° . All other reclining seating with leg rests shall be tested as tilting seating. With the seating in the fully reclined configuration, load the back of the seat with 8 loading discs and place 3 loading discs onto the leg rest at a distance Z from the intersection of the seat and back. Apply the loads for (120 ± 60) s. The seating shall not overturn.	NA
Reclining seating without leg rest (EN 1022:2018, 7.4.4)	The test method applies to all values of $\theta \geq 10^\circ$ and less than 45° and values of γ between 90° and 170° . All other reclining seating without foot rests shall be tested as tilting seating. Load the back of the seating with 8 loading discs and place 3 loading discs onto the front of the seat of the chair at a distance X from the intersection of the seat and back. Apply the loads for (120 ± 60) s. The seating shall not overturn.	PASS
Rearwards stability test for rocking chairs (EN 1022:2018, 7.4.5)	This test replaces the rearwards overturning test from 7.3.6. Load the chair with 8 loading discs so that the discs rest against the chair back. Move the chair forwards as far as is practicable or until the back is vertical. Allow the chair to rock rearwards freely under gravity. The seating shall not overturn.	NA
Loungers (EN 1022:2018, 8)		NA
Strength and durability (EN 12520:2015, 5.4) The strength and durability requirements are fulfilled when during and after testing in accordance with Table 1: a) there are no fractures of any member, joint or component; b) there are no loosening of joints intended to be rigid; c) seating fulfils its functions after removal of the test loads; d) seating fulfils the stability requirements.		
Seat static load and back static load test (EN 1728:2012, 6.4)	For seating without a back rest, only seat force shall be applied. Load seat not being tested with 750 N. Apply specified seat force 1300 N at the seat loading position. With the seat force maintained, apply specified back force 450N at back loading position or at 100 mm below the top of the back. When the back inclination θ is $\leq 55^\circ$ & $< 70^\circ$ to horizontal: Seat force F_1 (N) = $1300 \times \sin \theta$ Back force F_2 (N) = $(\theta/60^\circ - 0.1666) \times 1300 \times \cos \theta$ When the back inclination θ is $< 55^\circ$ to horizontal: Seat force F_1 (N) = 1300×0.75 Back force F_2 (N) = $1300 \times 0.75 \times \cos \theta$ Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce F_2 (min. 410N) to prevent rearwards overturning.	PASS
Seat front edge static load test (EN 1728:2012, 6.5)	Load seat not being tested with 750 N. Apply the force 1300 N at a point on the seat centre line 100 mm inwards from the front edge of the structure. Repeat the operation for 10 cycles, 10s each cycle. If the seating tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS



Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 6 of 11

Test Item	Test Method & Test Requirement	Test Result
Foot rest static load test (EN 1728:2012, 6.8)	Not apply to seating with a seat height $\leq 600\text{mm}$. Apply a downward force 750N to seat at the seat loading point. Apply a vertical force 1000N acting 80 mm from front edge of the load bearing structure of the foot rest at the point most likely to cause failure. For round cross section ring shaped footrests, apply the force through the centre of the ring cross section. Repeat the operation for 10 cycles, 10s each cycle. If the seating tends to overturn, increase the load on seat to a magnitude that just prevents overturning.	NA
Arm rest sideways static load test (EN 1728:2012, 6.10)	Apply an outward force 300N to one arm rest or to each arm rest of the unit simultaneously at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. Repeat the operation for 10 cycles, 10s each cycle.	NA
Arm rest downwards static load test (EN 1728:2012, 6.11)	Apply vertical force 700N to the arm rest or to both arm rests simultaneously at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. Repeat the operation for 10 cycles, 10s each cycle.	NA
Combined seat and back durability test (EN 1728:2012, 6.17)	For seating without a back rest, only seat force shall be applied. Load seat not being tested with 750 N. Apply specified seat force 1000N at the seat loading position. With the seat force maintained, apply specified back force 300N at back loading position or at 100 mm below the top of the back. When the back inclination θ is $\leq 55^\circ$ & $< 70^\circ$ to horizontal: Seat force F_3 (N) = $1000 \times \sin \theta$ Back force F_4 (N) = $(\theta/60^\circ - 0.1666) \times 1000 \times \cos \theta$ When the back inclination θ is $< 55^\circ$ to horizontal: Seat force F_3 (N) = 1000×0.75 Back force F_4 (N) = $1000 \times 0.75 \times \cos \theta$ Repeat the operation for 25000 cycles. If the item tends to overturn, reduce F_4 to prevent rearwards overturning.	PASS
Seat front edge durability test (EN 1728:2012, 6.18)	Apply the vertical force 800N alternately on two points each 80mm from the front edge of the seat structure and as near as possible to either side of the seat but not less than 80mm from the edges. Repeat the test for 20000 cycles. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS
Arm rest durability test (EN 1728:2012, 6.20)	Apply the force of 400 N on each arm rest at the point most likely to cause failure, but not less than 100 mm from the front or rear edge of the arm rest length and through the centre of the width of the arm rest, but not more than 100 mm from the inner edge of the arm rest. Repeat the test for 10000 cycles.	NA
Leg forward static load test (EN 1728:2012, 6.15)	Apply the seat load 1000N to all seat loading positions. Apply a horizontal force 400N centrally to the rear of the seat or to the rear of the most adverse seat position for seating with multiple seating positions, at seat level, in a forward direction. Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CTC (Shanghai) Technical Services Co., Ltd.
Anji Branch Hardlines

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t: (86-572) 5018825 f: (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t: (86-572) 5018825 f: (86-572) 5018829 e: sgs.china@sgs.com

Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 7 of 11

Test Item	Test Method & Test Requirement	Test Result
Leg sideways static load test (EN 1728:2012, 6.16)	Apply the seat load 1000N at a suitable position across the seat but not more than 150 mm from the unloaded edge of the seat. Apply a horizontal force 300N centrally to the unrestrained side of the seat, at seat level, in a direction towards the restrained feet. Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS
Seat impact test (EN 1728:2012, 6.24)	Allow the seat impactor to fall freely from a height 180 mm onto the seat loading position. Apply the operation for 10 cycles. Repeat the test at one other position considered likely to cause failure, but not less than 100 mm from any edge of the seat.	PASS
Backwards fall test (EN 1728:2012, 6.28)	This test is only for single seating units where the back will be the first part of the structure to strike the floor and the force used to overturn the chair rearwards is less than 30 N. Apply a rearward horizontal load to a point 50 mm below the top of the back rest in the centre of the back rest. Push the top of the back rest rearwards and allow it to fall freely on its back onto the rubber faced test floor without initial force or velocity. Repeat the operation for 5 cycles.	NA
Back impact test (EN 1728:2012, 6.25)	This test is for all seating not tested in accordance with Backwards Fall Test. With the front legs, feet or castors restrained by stops from moving forward, strike the structure of the centre of the top outside of the back with the impact hammer through a height 120 mm (or angle 28°). Repeat the operation for 10 cycles.	PASS
Information for use (EN 12520:2015, 6)		
Information for use (EN 12520:2015, 6)	Information for use shall be available in the language of the country in which it will be delivered to the end user. It shall contain at least the following details: a) assembly instructions, where applicable; b) instructions for the care and maintenance of the seating; c) if the seating is fitted with seat height adjustments with energy accumulators, an additional note is required pointing out that only trained personnel may replace or repair seat height adjustment components with energy accumulators.	NT

Remark:



1. NA = Not applicable; NT = Not tested



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

***Test Conducted: EN 1725:1998 Domestic furniture –Beds and mattresses – Safety requirements and test methods**

Test Result:



Test Item	Test Method & Test Requirement	Test Result
Safety requirements (EN 1725:1998, 6)		
Safety requirements (EN 1725:1998, 6)	All components or parts of the bed, with which the user may come into contact during normal use, shall not have burrs and/or sharp edges, nor shall there be open-ended tubes. When the bed is fully erected and ready for use, all accessible mechanisms that facilitate frame movement shall have safety distances between any two elements moving relative to each other which shall always be $\leq 8\text{mm}$ or $\geq 25\text{mm}$. When there is a specified danger of feet being trapped by a moving part, the safety distance shall always be $\geq 100\text{mm}$ from the floor. When tested according to 7.2, the test unit shall not overturn. All components shall pass the tests specified in clause 7 without fracture. After testing, there shall be no deformation that may compromise safety.	PASS
Test methods (EN 1725:1998, 7)		
Stability (EN 1725:1998, 7.2)	The test shall be carried out in accordance with EN 1022, except that the position of the loading points shall be as shown in Figure 6. Apply vertical force of 600N to the loading points and apply horizontal force of 20N from the loading points. 	PASS
Durability test (EN 1725:1998, 7.3)	Apply a vertical downward force of 1000 N at each position point shown in Figure 7. During each application maintain the load for $(3 \pm 1)\text{s}$. Repeat the test for 10000 cycles. In the case of an adjustable bed base, adjustable parts shall be in a position as close as possible to 7° above the horizontal. In the case of where the supporting structure of head and feet is identical, test shall be performed in the middle and to one end only. 	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t: (86-572) 5018825 f: (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t: (86-572) 5018825 f: (86-572) 5018829 e: sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
Vertical impact test (EN 1725:1998, 7.4)	Allow the impactor to fall freely from a height of 180 mm onto the mattress at the following positions (see Figure 8): - test units > 1150 mm in width: A, B, C, D, E, G, I and J; - test units ≤ 1150 mm in width: A, B, C, D, G, I and J; Carry out 10 impacts at each point. In the case of an adjustable bed base, adjustable parts shall be in a position as close as possible to 7° above the horizontal. In the case of where the supporting structure of head and feet is identical, test shall be performed in the middle and to one end only. The centre of the points A, C, D, G, I and J shall be located at 150 mm from the edge of the bed. 	PASS
Durability of bed edge (EN 1725:1998, 7.5)	Apply a force of 1000N on one edge at the middle of the length. The loading point shall be 200 mm from the edge of the top surface of the mattress. During each application maintain the load for (3±1)s. Repeat the test for 5000 cycles.	PASS
Vertical static load test (EN 1725:1998, 7.6)	Apply a vertical force of 1400N downwards at any point of the bed base where failure is considered likely to occur. Apply the force 10 times. During each application maintain the load for (10±1) s.	PASS
Vertical static load test of the edge of the bed (EN 1725:1998, 7.7)	Apply two forces of 1200N simultaneously for 1 min on the centre line of the bed frame side member. The loads shall be applied on points 600 mm apart, as shown in Figure 9. If the bed tends to overturn, the bed shall be loaded sufficiently to prevent from overturning. 	PASS

Test Report

No.: AJHL2102000422FT-01

Date: MAR 31, 2021

Page 10 of 11

***Test conducted: In accordance with EN 13759:2012 Furniture – Operating mechanisms for seating and sofa-beds – Test methods**

Test result:

Test Item	Test Requirements	Test Result
Durability	Operate the convertible sofa-bed for 3650 cycles. Requirement: No visible damage was found. Functional check was normal.	PASS

Remark:

- Operation action:
For convertible sofa-bed:
c) actions required to convert the bed into a sofa,
d) actions required to convert a sofa into a bed.
- The content remark with * was updated.

Sample Information

Overall dimension: 870 mm (L)×1800 mm (W)×805 mm (H)

Weight: 35.80 kg

Photo Appendix



Sample as received - View 1



Sample as received - View 2



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (China) Technical Services Co., Ltd.
Anji Branch Hardlines

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Member of the SGS Group (SGS SA)



Sample as received - View 3



Sample as received – View 4

SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com