

Test Report

No.: AJHL2004000688FT

Date: APR 23, 2020

Page 1 of 8

DOREL HOME FURNISHINGS EUROPE LTD

ALPHASON HOUSE, 244 SWAN LANE, HINDLEY GREEN, WIGAN WN2 4EY, UNITED KINGDOM


The following sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. Results apply to the sample as received.

Sample Description	OHIO LEATHER BARSTOOL-BLK
Style / Item No.	ABS249-BLK
Buyer Name	DOREL HOME FURNISHINGS EUROPE LTD
Manufacturer Name	LIAN LIANFENG FURNITURE CO LTD
Supplier Name	LIAN LIANFENG FURNITURE CO LTD
Country of Origin	CHINA
Country of Destination	UK
Sample Receiving Date	APR 16, 2020
Test Performing Date	APR 16, 2020 TO APR 23, 2020

Test Result Summary

Test(s) Requested	Result(s)
BS EN 12520:2015 Excluding Clause 6 information for use	PASS
Remark: 1. This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included. 2. For further details, please refer to the following page(s).	

Signed for and on behalf of
SGS-CSTC Co., Ltd. Anji Branch



scan to see the report



AJHL2004000688FT

David Fan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Report

No.: AJHL2004000688FT

Date: APR 23, 2020

Page 2 of 8

Test Conducted: BS EN 12520:2015 Furniture - Strength, durability and safety – Requirements for domestic seating

Test Result:

Test Item	Test Method & Test Requirement	Test Result
General requirements (BS EN 12520:2015, 5.1)		
General requirements (BS EN 12520:2015, 5.1)	All parts of the seating with which the user comes into contact, during intended use, shall be designed to ensure that physical injury and damage are avoided. These requirements are met when: a) edges of the seat, back rest and arm rests, which are in contact with the user when sitting are rounded or chamfered. All other edges accessible during use shall be free from burrs and/or sharp edges; b) ends of hollow components are closed or capped. Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided. It shall not be possible for any load bearing part of the seating to come loose unintentionally. All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.	PASS
Shear and squeeze points (BS EN 12520:2015, 5.2)		
Shear and squeeze points when setting up and folding (BS EN 12520:2015, 5.2.1)	Unless 5.2.2 or 5.2.3 are applicable, shear and squeeze points, as defined in 3.3, that are created only during setting up and folding, including tipping seat, are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain. The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 5.1.	PASS
Shear and squeeze points under the influence of powered mechanisms (BS EN 12520:2015, 5.2.2)	With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating under powered mechanisms e.g. springs and gas lifts. NOTE: Electrically operated seating is covered by EEC Directives for EMC, Machinery, Low Voltage or Medical Devices.	PASS
Shear and squeeze points during use (BS EN 12520:2015, 5.2.3)	There shall be no shear and squeeze points created by loads applied during normal use. The loads applied during normal use can be found in Table 1. Shear and squeeze points are not acceptable if a hazard is created by the weight of the user during normal movements and actions, e.g. attempting to move the seating by lifting the seat or by adjusting the backrest. NOTE: This hazard is best prevented by the use of automatic locking mechanisms.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
Stability (BS EN 12520:2015, 5.3)		
The seating shall fulfil the relevant requirements of BS EN 1022.		
All seating except loungers (BS EN 1022:2018, 7)		
General (BS EN 1022:2018, 7.1)	The stability tests are not applicable to seating which has both the height of the seat loading point < 200 mm and a mass < 5 kg.	/
Test procedures, all seating (BS EN 1022:2018, 7.3)		
Forwards overturning (BS EN 1022:2018, 7.3.1)	Apply a force F_1 of 600 N (for seating with multiple seats apply two forces simultaneously) vertically at the point on the centre line of the seat 60 mm behind the front edge of the load bearing structure. Apply a force F_2 of 20 N horizontally outwards from the point each vertical load contacts the seat surface for (5±2) s. For seating with a leg rest to support the weight of the user, repeat the test procedure on the leg rest with the leg rest fully extended. The seating shall not overturn.	PASS
Forwards overturning for seating with foot rest (BS EN 1022:2018, 7.3.2)	For seating with tubular foot rests or the foot rest depth is less than 120 mm, apply the vertical force F_1 of 1100 N at the most onerous point along the tube centre line or the middle of the foot rest surface. For all other seating with foot rests apply the vertical force F_1 of 1100 N at the most onerous point 60 mm from the edge of the foot rest. Apply a force F_2 of 20 N horizontally outwards from the point the vertical load contacts the foot rest surface for (5±2) s. The seating shall not overturn.	PASS
Corner stability test (BS EN 1022:2018, 7.3.3)	This test is only applicable on seating possible to apply the loading pad at the specified position. Define the loading point 60 mm from the edge of the load bearing structure on a line as specified at the corner. Apply a force F_1 of 300 N vertically at the loading point for (5±2) s. For seating with multiple seats apply the force F_1 at the loading point on one outside seating position. The seating shall not overturn.	PASS
Sideways overturning, all seating without arm rests (BS EN 1022:2018, 7.3.4)	This test is applicable to all seating where the top edge of the seat on the transverse plane is 50 mm or less above the height of the loaded seat loading point. Apply a force F_1 of 600 N vertically at a point 60 mm behind the edge of the load bearing structure on the side nearest the stopped feet and on the seat transverse plane. In the transverse plane, apply a sideways force F_2 of 20 N horizontally outwards from the point the vertical load contacts the seat surface for (5±2) s. The seating shall not overturn.	PASS



Test Item	Test Method & Test Requirement	Test Result
Sideways overturning, all other seating with arm rests (BS EN 1022:2018, 7.3.5.2)	This test is applicable to all seating with arms on the transverse plane is more than 50 mm above the seat loading point. Apply a force F_1 of 250 N vertically at a point 100 mm to the seat median plane nearest the stopped feet and on the transverse plane. Apply a force F_2 of 350 N vertically at a position on the centre line of the arm up to a maximum 40 mm inwards from the outside edge of arm structure on the transverse plane, but not less than 40 mm from the front or rear edge of the arm structure. If the transverse plane does not intersect with arm rest, apply force F_2 at 40 mm from the front or rear of the arm structure nearest the transverse plane. Apply a horizontal force F_3 of 20 N outwards and perpendicular to the line joining the stopped feet, for at least 5s, at the upper surface of the seat or arm rest in line with the vertical force F_2 . The seating shall not overturn.	NA
Sideways overturning, all other seating with raised side edges (BS EN 1022:2018, 7.3.5.3)	This test is applicable to all seating where the seat top edge on the transverse plane is more than 50 mm above the seat loading point. Apply a force F_1 of 250 N vertically at a point 100 mm to the seat median plane nearest the stopped feet and on the transverse plane. Apply a force F_2 of 350 N at a position no greater than 40 mm inwards from the outside edge of the raised edge on the side nearest the stopped feet and on the transverse plane. If the distance between the loading points is less than 200 mm, apply a force that provides the same overturning moment of the combined forces F_1 and F_2 at the most suitable point on the transverse plane. Apply a horizontal force F_3 of 20 N outwards and perpendicular to the line joining the stopped feet, for (5 ± 2) s, at the upper surface of the raised edge in line with vertical force F_2 . The seating shall not overturn.	NA
Rearwards overturning all seating with back rests (BS EN 1022:2018, 7.3.6)	The test is not applicable to seating that has adjustable back rest inclination that cannot be locked in position. Apply a vertical force F_1 of 600N to the seat at seat loading point. Apply the force F_2 ($F_2 = 80$ N if $H \geq 720$ mm; $F_2 = 0.2857(1000-H)$ N if $H < 720$ mm. H = Height of loaded seat above the floor, in mm) for (5 ± 2) s horizontally rearwards to the seating back at back loading point B, or at the top edge of back rest, whichever is the lower. When the seating has more than one sitting place, apply the procedure on two most adverse sitting places simultaneously. The seating shall not overturn.	PASS
Additional test procedures for seating with reclining back rests (BS EN 1022:2018, 7.4)		
Tilt chairs (BS EN 1022:2018, 7.4.2)	The test method applies to all values of $\theta \geq 10^\circ$ and values of γ between 90° and 170° . If the seating has a locking system it shall be disabled. Load the seat with 13 loading discs so that the discs are firmly settled against the back rest. Apply the loads for (120 ± 60) s. The seating shall not overturn.	NA
Reclining seating with leg rest (BS EN 1022:2018, 7.4.3)	No required load for swivelling seats.	NA



Test Report

No.: AJHL2004000688FT

Date: APR 23, 2020

Page 5 of 8

Test Item	Test Method & Test Requirement	Test Result
Reclining seating without leg rest (BS EN 1022:2018, 7.4.4)	No required load for swivelling seats.	NA
Rearwards stability test for rocking chairs (BS EN 1022:2018, 7.4.5)	No required load for swivelling seats.	NA
Loungers (BS EN 1022:2018, 8)		NA
Strength and durability (BS EN 12520:2015, 5.4) The strength and durability requirements are fulfilled when during and after testing in accordance with Table 1: a) there are no fractures of any member, joint or component; b) there are no loosening of joints intended to be rigid; c) seating fulfils its functions after removal of the test loads; d) seating fulfils the stability requirements.		
Seat static load and back static load test (BS EN 1728:2012, 6.4)	For seating without a back rest, only seat force shall be applied. Load seat not being tested with 750 N. Apply specified seat force 1300 N at the seat loading position. With the seat force maintained, apply specified back force 450N at back loading position or at 100 mm below the top of the back. When the back inclination θ is $\leq 55^\circ$ & $< 70^\circ$ to horizontal: Seat force F_1 (N) = $1300 \times \sin \theta$ Back force F_2 (N) = $(\theta/60^\circ - 0.1666) \times 1300 \times \cos \theta$ When the back inclination θ is $< 55^\circ$ to horizontal: Seat force F_1 (N) = 1300×0.75 Back force F_2 (N) = $1300 \times 0.75 \times \cos \theta$ Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce F_2 (min. 410N) to prevent rearwards overturning.	PASS
Seat front edge static load test (BS EN 1728:2012, 6.5)	Load seat not being tested with 750 N. Apply the force 1300 N at a point on the seat centre line 100 mm inwards from the front edge of the structure. Repeat the operation for 10 cycles, 10s each cycle. If the seating tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS
Foot rest static load test (BS EN 1728:2012, 6.8)	Not apply to seating with a seat height ≤ 600 mm. Apply a downward force 750N to seat at the seat loading point. Apply a vertical force 1000N acting 80 mm from front edge of the load bearing structure of the foot rest at the point most likely to cause failure. For round cross section ring shaped footrests, apply the force through the centre of the ring cross section. Repeat the operation for 10 cycles, 10s each cycle. If the seating tends to overturn, increase the load on seat to a magnitude that just prevents overturning.	PASS
Arm rest sideways static load test (BS EN 1728:2012, 6.10)	Apply an outward force 300N to one arm rest or to each arm rest of the unit simultaneously at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. Repeat the operation for 10 cycles, 10s each cycle.	NA



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t: (86-572) 5018825 f: (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t: (86-572) 5018825 f: (86-572) 5018829 e: sgs.china@sgs.com

Test Report

No.: AJHL2004000688FT

Date: APR 23, 2020

Page 6 of 8

Test Item	Test Method & Test Requirement	Test Result
Arm rest downwards static load test (BS EN 1728:2012, 6.11)	Apply vertical force 700N to the arm rest or to both arm rests simultaneously at the points along the arm rest most likely to cause failure, but not less than 100 mm from the end of the arm rest structure. Repeat the operation for 10 cycles, 10s each cycle.	NA
Combined seat and back durability test (BS EN 1728:2012, 6.17)	For seating without a back rest, only seat force shall be applied. Load seat not being tested with 750 N. Apply specified seat force 1000N at the seat loading position. With the seat force maintained, apply specified back force 300N at back loading position or at 100 mm below the top of the back. When the back inclination θ is $\leq 55^\circ$ & $< 70^\circ$ to horizontal: Seat force F_3 (N) = $1000 \times \sin \theta$ Back force F_4 (N) = $(\theta/60^\circ - 0.1666) \times 1000 \times \cos \theta$ When the back inclination θ is $< 55^\circ$ to horizontal: Seat force F_3 (N) = 1000×0.75 Back force F_4 (N) = $1000 \times 0.75 \times \cos \theta$ Repeat the operation for 25000 cycles. If the item tends to overturn, reduce F_4 to prevent rearwards overturning.	PASS
Seat front edge durability test (BS EN 1728:2012, 6.18)	Apply the vertical force 800N alternately on two points each 80mm from the front edge of the seat structure and as near as possible to either side of the seat but not less than 80mm from the edges. Repeat the test for 20000 cycles. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	PASS
Arm rest durability test (BS EN 1728:2012, 6.20)	Apply the force of 400 N on each arm rest at the point most likely to cause failure, but not less than 100 mm from the front or rear edge of the arm rest length and through the centre of the width of the arm rest, but not more than 100 mm from the inner edge of the arm rest. Repeat the test for 10000 cycles.	NA
Leg forward static load test (BS EN 1728:2012, 6.15)	Apply the seat load 1000N to all seat loading positions. Apply a horizontal force 400N centrally to the rear of the seat or to the rear of the most adverse seat position for seating with multiple seating positions, at seat level, in a forward direction. Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	NA
Leg sideways static load test (BS EN 1728:2012, 6.16)	Apply the seat load 1000N at a suitable position across the seat but not more than 150 mm from the unloaded edge of the seat. Apply a horizontal force 300N centrally to the unrestrained side of the seat, at seat level, in a direction towards the restrained feet. Repeat the operation for 10 cycles, 10s each cycle. If the item tends to overturn, reduce the force to a magnitude that just prevents overturning.	NA
Seat impact test (BS EN 1728:2012, 6.24)	Allow the seat impactor to fall freely from a height 180 mm onto the seat loading position. Apply the operation for 10 cycles. Repeat the test at one other position considered likely to cause failure, but not less than 100 mm from any edge of the seat.	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Test Item	Test Method & Test Requirement	Test Result
Backwards fall test (BS EN 1728:2012, 6.28)	This test is only for single seating units where the back will be the first part of the structure to strike the floor and the force used to overturn the chair rearwards is less than 30 N. Apply a rearward horizontal load to a point 50 mm below the top of the back rest in the centre of the back rest. Push the top of the back rest rearwards and allow it to fall freely on its back onto the rubber faced test floor without initial force or velocity. Repeat the operation for 5 cycles.	PASS
Back impact test (BS EN 1728:2012, 6.25)	This test is for all seating not tested in accordance with Backwards Fall Test. With the front legs, feet or castors restrained by stops from moving forward, strike the structure of the centre of the top outside of the back with the impact hammer through a height 120 mm (or angle 28°). Repeat the operation for 10 cycles.	NA
Information for use (BS EN 12520:2015, 6)		
Information for use (BS EN 12520:2015, 6)	Information for use shall be available in the language of the country in which it will be delivered to the end user. It shall contain at least the following details: a) assembly instructions, where applicable; b) instructions for the care and maintenance of the seating; c) if the seating is fitted with seat height adjustments with energy accumulators, an additional note is required pointing out that only trained personnel may replace or repair seat height adjustment components with energy accumulators.	NP

Remark:

1. NA = Not applicable; NP = Not provided



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC (China) Technical Services Co., Ltd.
Anji Branch Hardlines

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

Sample Information

Overall dimension: 475 mm (L)×450 mm (W)×670 mm -885 mm (H)

Diameter of base: 450 mm

Weight: 6.50 kg

Photo Appendix



Sample as received - View 1



Sample as received - View 2



Sample as received - View 3



Sample as received - View 4

SGS authenticate the photo on original report only

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com