

TEST REPORT

No.: AJFTS25001271R05_EN

Date: Mar 21,2025

Page 1 of 5

ZHE JIANG WUXING FURNITURE CO., LTD
BLOCK, SUNLIGHT INDUSTRY ZONE, ANJI COUNTY, ZHE JIANG PROVINCE, CHINA

Sample Description : FOAM
Style/Item No. : MARCELA SET OF 2 CHAIRS/ ER21342-18
Client Reference Information : MARCELA BAR STOOL/ ER21342-26 OREN SWIVEL CHAIR AND FOOT STOOL CHENILLE GREY/JFR22005 KARA SWIVEL CHAIR AND FOOT STOOL CHENILLE IVORY/JFR21027B-2
Supplier Name : ZHE JIANG WUXING FURNITURE CO., LTD
Manufacturer Name : ZHE JIANG WUXING FURNITURE CO., LTD
Country of Origin : CHINA
Country of Destination : UK

The above sample(s) data and information was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

SGS Ref. No. : AJHL2503001205FT
Sample Receiving Date : Mar 13,2025
Testing Period : Mar 13,2025 to Mar 20,2025
Test Required : The Furniture and Furnishings (Fire) (Safety) Regulations 1988 S.I. No. 1324 (amended 1989, 1993 and 2010), Schedule 1 Part I Ignitability test for foam in slab or cushion form.
 As specified in above standard(s) and incorporated with using ignition source 5 of BS 5852 Part 2:1982.
Test result(s) : See attached sheet
Conclusion : The tested sample **meets** the requirements of Schedule 1 Part I in Statutory Instrument 1988 No. 1324 (Amended 1989, 1993 and 2010) the Furniture and Furnishings (Fire) (Safety) Regulations.

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd Anji Branch



Echo Li
Approved signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 sgs.china@sgs.com

Test Conducted

The Furniture and Furnishings (Fire) (Safety) Regulations 1988 S.I. No. 1324 (amended 1989,1993 and 2010), Schedule 1 Part I Ignitability test for foam in slab or cushion form.

Crib 5 test (Ignition Source 5) of BS 5852 Part 2:1982.

Conditioning

The cribs and specimens were conditioned for 72 h in indoor ambient conditions and then immediately before the test for at least 16 h in an atmosphere having a temperature of 20±5°C and a relative humidity of 50±20%.

At time of testing: Temperature between 15°C ~ 30°C and Relative humidity between 20% ~ 70%.

Test Result

The following test results relate only to the ignitability of the combination of materials under the particular condition of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

(A) Progressive smouldering

Criteria of failure (Clause 4.1 of BS 5852 Part 2:1982)	1 st	2 nd
4.1 b) Any composite that product externally detectable amounts of smoke, heat or glow 60 min after ignition of the crib.	No	No
4.1 c) Any composite that displays escalating combustion behaviour so that it is unsafe to continue the test and requires forcible extinction.	No	No
4.1 d) Any composite that smoulders until it is essentially consumed within the test duration relevant to the source.	No	No
4.1 e) Any composite that smoulders to the extremities of the specimen viz. upper or lower margins, either side or to its full thickness, within the duration of the test.	No	No
4.1 f) Any composite that, on the final examination, shows evidence of charring other than discolouration, more than 100 mm in any direction apart from upwards from the nearest part of the original position of the source.	No	No



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

(B) Flaming

Criteria of failure (Clause 4.2 of BS 5852 Part 2:1982)	1 st	2 nd
4.2 b) Any composite that continues to flame for more than 10 minutes after the ignition of the crib.	No	No
4.2 d) Any composite that displays escalating combustion behaviour so that it is unsafe to continue the test and forcible extinction is required.	No	No
4.2 e) Any composite that burns until it is essentially consumed within the test duration relevant to the source.	No	No
4.2 f) Any composite on which any flame front reaches the lower margin, either side or passes through the full thickness of the specimen within the duration of the test.	Yes	Yes

(C) Mass Loss

Criteria (Clause 5 in Schedule 1 of UK Regulations)	1 st	2 nd
If failure against the criteria of clause 4 of BS 5852: Part 2 has occurred but only by way of damage exceeding the limits defined in clause 4.1(e), 4.1(f) and 4.2(f) and provided that the resultant mass loss is less than 60g the foam passes the ignitability test.	28 g	31 g



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Detailed Results

Test No.		1 st	2 nd
Progressive smouldering (PS) or Flaming (F)		No	No
Duration of	Ignition source (min, s)	2 min 10 s	2 min 18 s
	Flames (min, s)	2 min 45 s	2 min 59 s
	Smoke (min, s)	3 min 40 s	3 min 55 s
Extent of damage of horizontal component	Foam - Width (mm)	112	117
	Foam - Length (mm)	177	181
	Foam - Depth (mm)	Through	Through
Extent of damage of vertical component	Foam - Width (mm)	137	142
	Foam - Depth (mm)	56	59
Damage exceeds limits of clauses 4.1(e), 4.1(f) or 4.2(f)		Yes,4.2(f)	Yes,4.2(f)
Initial weight before test (g)		5827	5838
Final weight after test (g)		5799	5807
Resultant mass loss (g)		28	31
Reason for failure (Ref to failure code)		---	---
Final examination of progressive smouldering (9.4)		No	No
Comments & observations		No	No
Result		Pass	Pass

Statement: The decision rules for statements of conformity (Pass/Fail) have been applied to any results that results in a numerical value and are based on the probability conformance of 95% (UKAS LAB 48) agreed with the customer at the contract review stage.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Photo Appendix:

Details of sample:

Color: Blue

This foam sample of approximate density of 26.7 kg/m³.



SGS authenticate the photo on original report only

*** End of Report ***

